

G086FRMBHF-18

Connector 2

GPPO (SMPM) Fem Jack Swept RA 65 GHz

Connector 1

GPPO (SMPM) Male Bulkhead Plug 65 GHz



Length Dimensions inch/cm **Cable Type:** 0.086" Hand Formable, RoHS

Overall end-to-end: 18/45.72 Jacket: None

Between Ref. Planes: 17.86/45.37 Length: 18 inches long overall

Less Connectors: 17.38/44.15 Phase matching: N/A

C1 Ref. Plane (R/P): 0.05/0.14 **Test Data:** N/A **C2 Ref. Plane (R/P):** 0.08/0.21 **Rotation:** N/A

Cable Marker typically placed center cable includes P/N, Serial, and Manufacturer

These specifications are subject to change without notice.

Component images are not to scale.

SPECIFICATIONS:

FREQUENCY RANGE: DC to 65 GHZ

RETURN LOSS: Unspecified

INSERTION LOSS (up to above frequency limit): <1.1 dB/ft @ 18 GHz, <1.4 dB/ft @ 27 GHz, <2.0 dB/ft @ 40 GHz, <2.4

dB/ft @67 GHz (typical), +0.3 dB per connector

CONNECTOR 1: GPPO/SMPM F, direct solder, swept right angle, genuine Corning Gilbert P/N: B015-D11-01, or equivalent

CONNECTOR 2: GPPO/SMPM M, direct solder, straight, bulkhead, genuine Corning Gilbert P/N: B016-D33-01

CABLE TYPE: Hand-Formable (tin-dipped woven copper braid outer conductor), (magnetic steel wire center conductor),

0.086" (2.2mm) diameter nominal, Micro-Coax P/N: UT-85-Form (select 67 GHz stocks), or equivalent **MINIMUM INSIDE BEND RADIUS:** 0.125" (3.2mm) installation, 0.375" (9.5mm) continuous flexing **SOLDER:** 96.5Sn3.0Ag0.5Cu (SAC305) Pb-free, COMPLIANT WITH EU Directive RoHS 3 (2015/863)

RF COAX INC.

1725 San Felipe Road, Suite 3 Hollister, CA 95023 USA TEL: 831-635-0820, FAX: 831-785-2990 sales@rfcoax.com www.rfcoax.com All rights reserved

File No: 0.05/0.11,17.64/44.8,0.06/0.15

CAGE 1WF56

RF Cable Assembly, GPPO F RA to GPPO M BH, 0.086 hand-formable, 65 GHz, 18-inches long overall, RoHS

TYPE: Product Specification

REVISION: A **Date**: 07/17/2025

Item: G086FRMBHF-18